SAYBR TWO DEPARTURE (RNAV)


D-ATIS 124.4 CLNC DEL 125.5 263.0 CPDLC GND CON 121.9 348.6 AUSTIN TOWER 121.0 281.5 AUSTIN DEP CON 127.225 317.65

TOP ALTITUDE: ASSIGNED BY ATC

TAKEOFF MINIMUMS:

Rwys 17L/R: Standard.

Rwys 35L/R: Standard with minimum climb of 240' per NM to 2600.



NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

5000

NOTE: RNAV-1.

NOTE: For DFW terminal area arrivals at FL230 or below only.

SAYBR

NOTE: Chart not to scale.

V

SC-3, 16 JUL 2020 to 13 AUG 2020

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWYS 17L/R: Climb heading 175° or as assigned by ATC for RADAR vectors to cross MUNCH at or above 5000, thence

TAKEOFF RWYS 35L/R: Climb heading 355° or as assigned by ATC for RADAR vectors to cross MUNCH at or above 5000, thence

.... on track 024° to SAYBR. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.